

View Online at <https://aerobasegroup.com/nsn/5950-00-800-7254>

Reliability Indicator:

Not established

Inductance Rating:

31.00 millihenries single component single secondary

Impedance Rating In Ohms:

100.0 single component single secondary

Frequency Rating:

900.0 hertz single component

Primary To Secondary Turn Ratio:

1-13/32 to 1 single component

Pulse Repetition Rate:

1.5 kilohertz single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 1.875 inches and 2.001 inches

Body Outside Diameter:

Between 1.687 inches and 1.813 inches

Maximum Operating Temp:

105.0 degrees celsius

Distance Between Mounting Facility Centers:

1.094 inches single mounting facility single center group and 1.156 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches single group

Dc Resistance Rating In Ohms:

2.300 single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0