

View Online at <https://aerobasegroup.com/nsn/5950-00-802-3846>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.187 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.250 inches

Body Width:

2.000 inches

Body Height:

2.250 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary, variable autotransformer type single component

Winding Operating Voltage:

106.25 ac kilovolts single component single primary output and 21.25 ac volts single component single primary output and 318.75 ac kilovolts single component single primary output and 42.50 ac volts single component single primary output and 531.25 ac kilovolts single component single primary output and 63.75 ac volts single component single primary output and 743.75 ac kilovolts single component single primary output and 85.00 ac volts single component single primary output and 110.00 ac volts single component single primary output

Terminal Type And Quantity:

11 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0