

View Online at <https://aerobasegroup.com/nsn/5950-00-803-3016>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.812 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

3.500 inches

Body Width:

2.937 inches

Body Height:

2.562 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

3.0 amperes ac single component 2nd secondary

Winding Operating Voltage:

52.00 ac volts single component 3rd secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0