## NSN 5950-00-804-2916

Power Transformer - Page 1 of 2

Reliability Indicator:

Not established



View Online at https://aerobasegroup.com/nsn/5950-00-804-2916

Overall Length:
3.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.875 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.375 inches single mounting facility single center group
Overall Width:
3.250 inches
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core single component
Body Height:
4.625 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 9 secondary single component
Thread Size:
0.190 inches single group
Winding Operating Current:
4.15 amperes ac single component 3rd secondary
Winding Power Rating:
6.615 volts-amperes single component 4th secondary
Winding Operating Voltage:
6.30 ac volts single component 3rd secondary
Thread Series Designator:
Unf single group
Terminal Type And Quantity:
22 turret
Shelf Life:
N/a
Unit Of Measure:

## NSN 5950-00-804-2916

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0