NSN 5950-00-807-2749

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-807-2749

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.984 inches single mounting facility single center group and 3.016 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.984 inches single mounting facility single center group and 3.016 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.484 inches

Body Width:

4.110 inches

Body Height:

Between 3.062 inches and 3.438 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

300.0 milliamperes ac single component 3rd secondary

Winding Power Rating:

3.2 volts-amperes single component 2nd secondary

Winding Operating Voltage:

416.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 turret

NSN 5950-00-807-2749

Power Transformer - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0