## NSN 5950-00-807-7184

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-807-7184

### Reliability Indicator:

Not established

#### **Frequency Rating:**

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### Winding Shielding Method:

Internal shield grounded to inclosure and core single component

**Body Length:** 

2.406 inches

Body Width:

2.156 inches

Body Height:

2.125 inches

#### **Distance Between Mounting Facility Centers:**

0.938 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

**Mounting Facility Quantity:** 

2 single group

**Mounting Method:** 

Threaded stud single group

#### Winding Function And Quantity:

1 primary single component and 2 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

#### Winding Operating Current:

3.6 amperes ac single component 2nd secondary

#### Winding Operating Voltage:

6.40 ac volts single component all secondary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

6 standoff, wire lead

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

# **NSN 5950-00-807-7184** Power Transformer - Page 2 of 2

Fiig: A058b0

