NSN 5950-00-807-8747

Power Transformer - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5950-00-807-6747 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.375 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.000 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 1.906 inches |
| Body Width: |
| 1.531 inches |
| Body Height: |
| 1.344 inches |
| Maximum Operating Temp: |
| 85.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 40 single group |
| Thread Size: |
| 0.112 inches single group |
| Winding Operating Current: |
| 60.0 milliamperes ac single component 2nd secondary |
| Winding Operating Voltage: |
| 6.30 ac volts single component 1st secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 8 turret |
| Shelf Life: |
| N/a |
| Unit Of Massura: |

NSN 5950-00-807-8747

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0