## NSN 5950-00-809-4652

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-809-4652
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
7.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
5.000 inches single mounting facility single center group
Mounting Hole Diameter:
0.375 inches single group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Inclosure Type:
Partially enclosed, double shell
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Power Rating:
1.0 kilovolt-amperes single component single secondary
Winding Operating Voltage:
28.00 ac volts single component single secondary
Test Data Document:
81349-mil-t-15108 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
4 threaded stud
Specification Or Standard:
Id type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A058b0