

View Online at <https://aerobasegroup.com/nsn/5950-00-810-5779>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.437 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.687 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

2.310 inches

Body Width:

2.060 inches

Body Height:

3.120 inches

End Application:

Landing system automatic carrier, dual channel, nimitz class cvn, forrestal class cv, general purpose electronic test equipment gpete, an/spn-42t-3, 42t-4, and an/spn-46 (v) 1

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

290.0 milliamperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

200.00 ac volts single component single primary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0