## NSN 5950-00-811-8438

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-811-8438

| Reliability Indicator:   |
|--|
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                            |
| 2.297 inches single mounting facility single center group  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                             |
| 1.859 inches single mounting facility single center group  |
| Frequency Rating:  |
| 60.0 hertz single component  |
| Input-output Phase Relationship:   |
| Three phase to three phase single component  |
| Body Length:   |
| 3.060 inches   |
| Body Width:  |
| 2.620 inches   |
| Body Height:   |
| 4.250 inches   |
| Inclosure Type:  |
| Hermetically sealed  |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Threaded stud single group   |
| Winding Function And Quantity:   |
| 1 primary single component and 1 secondary single component  |
| Thready Qty Per Inch (tpi):  |
| 32 single group  |
| Thread Size:   |
| 0.164 inches single group  |
| Winding Operating Voltage:   |
| 8.76 ac volts single component single secondary and 11.70 ac volts single component single secondary |
| Thread Series Designator:  |
| Unc single group   |
| Terminal Type And Quantity:  |
| 12 tab, solder lug   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A058b0   |