NSN 5950-00-812-0276

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-812-0276

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.750 inches single mounting facility single center group |
| Frequency Rating: |
| 50.0 hertz single component or 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 4.500 inches |
| Body Width: |
| 3.750 inches |
| Body Height: |
| 5.050 inches |
| Inclosure Type: |
| Partially enclosed, double shell |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 11 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 24 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |