

View Online at <https://aerobasegroup.com/nsn/5950-00-812-2205>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.687 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.656 inches

Body Width:

3.937 inches

Body Height:

5.250 inches

End Application:

Iwo jima class lph; kidd class ddg; virginia class cgn (41); sturgeon class ssn (637); nimitz class cvn; wasp class lhd; general purpose electronic test equipment gpete; forrestal class cv; emory s. Land class as

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 6 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

200.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

63.00 ac volts single component 3rd secondary

Special Features:

1primary winding; 6secondary windings; primary can operate in series or parallel

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0