

View Online at <https://aerobasegroup.com/nsn/5950-00-812-2205>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.687 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component and 1.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

4.656 inches

**Body Width:**

3.937 inches

**Body Height:**

5.250 inches

**End Application:**

Iwo jima class lph; kidd class ddg; virginia class cgn (41); sturgeon class ssn (637); nimitz class cvn; wasp class lhd; general purpose electronic test equipment gpete; forrestal class cv; emory s. Land class as

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

2 primary single component and 6 secondary single component

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

200.0 milliamperes ac single component 1st secondary

**Winding Operating Voltage:**

63.00 ac volts single component 3rd secondary

**Special Features:**

1primary winding; 6secondary windings; primary can operate in series or parallel

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

16 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0