

View Online at <https://aerobasegroup.com/nsn/5950-00-816-0263>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.109 inches single mounting facility single center group and 1.141 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.797 inches single mounting facility single center group and 0.829 inches single mounting facility single center group

Overall Height:

1.313 inches

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 1.484 inches and 1.516 inches

Body Width:

1.125 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

1.5 milliamperes ac single component 3rd secondary

Winding Power Rating:

0.009 volts-amperes single component 1st secondary

Winding Operating Voltage:

6.00 ac volts single component 4th secondary

Special Features:

One primary winding; seven secondary windings, with third, fourth, and seventh secondary center tapped

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

21 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0