

View Online at <https://aerobasegroup.com/nsn/5950-00-820-1498>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.172 inches single mounting facility all center groupings and 1.203 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.172 inches single mounting facility all center groupings and 1.203 inches single mounting facility all center groupings

Overall Height:

2.820 inches

Impedance Rating In Ohms:

600.0 single component single secondary

Frequency Rating:

300.0 hertz single component and 3.5 kilohertz single component

Maximum Transformer Power Rating:

3.0 milliwatts single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 1.560 inches and 1.630 inches

Body Width:

Between 1.560 inches and 1.630 inches

Body Height:

Between 2.250 inches and 2.380 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches all groupings

Winding Operating Current:

60.0 milliamperes dc single component single primary

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0