NSN 5950-00-821-8455

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-821-8455

| view Offilitie at https://aerobasegroup.com/hsh/5550-00-021-0455 |
|--|
| Thread Class (non-core): |
| 2a single group |
| Thread Direction (non-core): |
| Right-hand single group |
| Reliability Indicator: |
| Not established |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.812 inches |
| Body Width: |
| 1.500 inches |
| Body Height: |
| 3.375 inches |
| Distance Between Mounting Facility Centers: |
| 2.124 inches single mounting facility single center group |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.112 inches single group |
| Winding Operating Current: |
| 12.0 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 6.30 ac pounds per hour wet single component single secondary |
| Thread Series Designator: |
| Uns single group |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-00-821-8455

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0