## NSN 5950-00-822-5612

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-822-5612

| Reliability Indicator:  |
|---|
| Not established   |
| Overall Length:   |
| 1.937 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 1.375 inches single mounting facility single center group   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.250 inches single mounting facility single center group   |
| Overall Height:   |
| 2.437 inches  |
| Overall Width:  |
| 1.812 inches  |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure single component  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component   |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.138 inches single group   |
| Winding Operating Current:  |
| 120.0 milliamperes ac single component single secondary and 180.0 milliamperes ac single component single secondary and 220.0   |
| milliamperes ac single component single secondary and 400.0 milliamperes ac single component single secondary                   |
| Winding Operating Voltage:  |
| 24.00 ac volts single component single secondary and 26.00 ac volts single component single secondary and 30.00 ac volts single |
| component single secondary and 34.00 ac volts single component single secondary   |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 7 tab, solder lug   |
| Shelf Life:   |
| N/a   |

--

**Unit Of Measure:** 

## NSN 5950-00-822-5612

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0