NSN 5950-00-822-8370

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-822-8370 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.250 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.375 inches single mounting facility single center group |
| Overall Height: |
| 2.780 inches |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 1.940 inches |
| Body Width: |
| 1.820 inches |
| Body Height: |
| 2.440 inches |
| Maximum Operating Temp: |
| 50.0 degrees celsius |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 8 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Voltage: |
| 65.00 ac volts single component single secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 4 turret |
| Shelf Life: |

N/a

NSN 5950-00-822-8370

Power Transformer - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0