

View Online at <https://aerobasegroup.com/nsn/5950-00-823-3174>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to three phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

1.625 inches

Body Width:

0.832 inches

Body Height:

2.094 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

3 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

1.260 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.562 inches single mounting facility single center group

Winding Operating Voltage:

6.90 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

18 solder stud

Reference Number Differentiating Characteristics:

Selected and tested for navigational systems

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0