NSN 5950-00-823-3206

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-823-3206

| View Online at https://aerobasegroup.com/nsn/5950-00-823-3206 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.625 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.125 inches single mounting facility single center group |
| Overall Height: |
| 5.250 inches |
| Inductance Type: |
| Swinging |
| Inductance Rating: |
| 800.00 millihenries single component all winding and 4.50 henry single component all winding |
| Body Length: |
| 3.562 inches |
| Body Width: |
| 3.062 inches |
| Body Height: |
| 4.875 inches |
| Winding Quantity: |
| 2 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.164 inches single group |
| Winding Operating Current: |
| 2750.0 milliamperes dc single component single winding and 15.0 amperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 0.015 single component all winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 4 standoff, solder lug |
| Shelf Life: |

N/a

NSN 5950-00-823-3206

Reactor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0