

View Online at <https://aerobasegroup.com/nsn/5950-00-823-3263>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.560 inches

Body Width:

3.060 inches

Body Height:

3.880 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

283.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

50.00 ac volts single component 3rd secondary

Special Test Features:

Navord od41152

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 tab, solder lug

Reference Number Differentiating Characteristics:

As differentiated by special testfeatures

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0