# NSN 5950-00-824-0666

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-824-0666

## Reliability Indicator:

Not established

## **Frequency Rating:**

400.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single component

### Winding Shielding Method:

Internal shield grounded to inclosure single component

#### **Body Length:**

1.312 inches

**Body Width:** 

1.312 inches

#### **Body Height:**

1.750 inches

#### **Distance Between Mounting Facility Centers:**

1.250 inches single mounting facility single center group

### Inclosure Type:

Fully enclosed

## **Mounting Facility Quantity:**

2 single group

## Mounting Method:

Threaded stud single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

### Thready Qty Per Inch (tpi):

32 single group

### Thread Size:

0.138 inches single group

## Winding Operating Current:

200.0 milliamperes ac single component single secondary

#### Winding Operating Voltage:

30.00 ac volts single component single secondary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

4 turret

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5950-00-824-0666

Power Transformer - Page 2 of 2

**Fiig:** A058b0

