

View Online at <https://aerobasegroup.com/nsn/5950-00-824-4952>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.770 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.370 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Body Length:

3.750 inches

Body Width:

2.000 inches

Body Height:

2.500 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

1.2 amperes ac single component single primary output and 250.0 milliamperes ac single component single primary output and 800.0 milliamperes ac single component single primary output and 160.0 milliamperes ac single component single primary output

Winding Power Rating:

137.0 volts-amperes single component single primary input

Winding Operating Voltage:

8.70 ac volts single component single primary output and 15.00 ac volts single component single primary output and 26.00 ac volts single component single primary output and 66.50 ac volts single component single primary output

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0