NSN 5950-00-824-6874

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-824-6874

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 2.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.906 inches single mounting facility single center group Mounting Slot Width: 0.187 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary Terminal Type And Quantity:
Center To Center Distance Between Mounting Facilities Parallel To Length: 2.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.906 inches single mounting facility single center group Mounting Slot Width: 0.187 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component single primary and 115.00 ac volts single component single primary
2.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.906 inches single mounting facility single center group Mounting Slot Width: 0.187 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component single primary and 115.00 ac volts single component single primary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Center To Center Distance Between Mounting Facilities Parallel To Width: 0.906 inches single mounting facility single center group Mounting Slot Width: 0.187 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Mounting Slot Width: 0.187 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component single primary and 115.00 ac volts single component single primary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Mounting Slot Width: 0.187 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component single primary and 115.00 ac volts single component single primary
Single phase to single phase single component Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component single primary and 115.00 ac volts single component single primary
Body Length: 3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
3.500 inches Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Body Width: 1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
1.625 inches Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Body Height: 3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
3.000 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
1 primary single component and 3 secondary single component Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Winding Operating Current: 580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
580.0 milliamperes ac single component 3rd secondary Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Winding Operating Voltage: 93.00 ac volts single component single primary and 115.00 ac volts single component single primary
93.00 ac volts single component single primary and 115.00 ac volts single component single primary
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A058b0