

View Online at <https://aerobasegroup.com/nsn/5950-00-824-7735>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

1.937 inches

Body Width:

1.812 inches

Body Height:

2.437 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

120.0 milliamperes ac single component single secondary and 400.0 milliamperes ac single component single secondary and 180.0 milliamperes ac single component single secondary and 220.0 milliamperes ac single component single secondary and 50.0 milliamperes ac single component single secondary

Winding Operating Voltage:

21.00 ac volts single component single secondary and 26.00 ac volts single component single secondary and 30.00 ac volts single component single secondary and 34.00 ac volts single component single secondary and 115.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0