NSN 5950-00-825-2505

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-825-2505

| Reliability Indicator: |
|---|
| Not established |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 2.468 inches |
| Body Width: |
| 2.218 inches |
| Body Height: |
| 2.343 inches |
| Maximum Operating Temp: |
| 75.0 degrees celsius |
| Distance Between Mounting Facility Centers: |
| 0.938 inches single mounting facility single center group |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 20.0 amperes ac single component 3rd secondary |
| Winding Operating Voltage: |
| 6.40 ac volts single component all secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-00-825-2505

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0