

View Online at <https://aerobasegroup.com/nsn/5950-00-827-3324>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.281 inches

Body Width:

3.625 inches

Body Height:

3.875 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Cubic Measure (non-core):

46.0 cubic inches

Winding Operating Current:

3.0 amperes ac single component 3rd secondary

Winding Power Rating:

87.5 volts-amperes single component 2nd secondary

Winding Operating Voltage:

6.30 ac pounds per hour wet single component 1st secondary

Unpackaged Unit Weight (non-core):

6.000 pounds

Terminal Type And Quantity:

10 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0