## NSN 5950-00-829-3109

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-829-3109

Reliability Indicator:
lot established
Center To Center Distance Between Mounting Facilities Parallel To Lengt
8.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width
.250 inches single mounting facility single center group
requency Rating:
i4.0 hertz single component and 880.0 hertz single component
nput-output Phase Relationship:
hree phase to three phase single component
Vinding Shielding Method:
nternal shield brought out to terminal single component
Body Length:
.000 inches
Body Width:
.625 inches
Body Height:
.750 inches
nclosure Type:
Fully enclosed
Nounting Facility Quantity:
single group
Nounting Method:
hreaded stud single group
Vinding Function And Quantity:
primary single component and 1 secondary single component
hready Qty Per Inch (tpi):
2 single group
hread Size:
0.164 inches single group
Vinding Operating Current:
25.0 milliamperes ac single component single secondary
Vinding Operating Voltage:
0.00 ac volts single component single primary
Thread Series Designator:
Inc single group
erminal Type And Quantity:
wire hook
Shelf Life:
l/a
Jnit Of Measure:
-

## NSN 5950-00-829-3109

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

