

View Online at <https://aerobasegroup.com/nsn/5950-00-834-3331>

Reliability Indicator:

Not established

Overall Length:

2.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.937 inches single mounting facility single center group

Overall Height:

1.060 inches

Overall Width:

1.250 inches

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

30.0 milliamperes ac single component 3rd secondary and 55.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0