NSN 5950-00-834-5089

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-834-5089

g
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.094 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
.500 inches single mounting facility single center group
Frequency Rating:
100.0 hertz single component
nput-output Phase Relationship:
Single phase to single phase single component
Body Length:
2.938 inches
Body Width:
2.750 inches
Body Height:
2.875 inches
nclosure Type:
Fully enclosed
Mounting Facility Quantity:
l single group
Mounting Method:
Threaded hole single group
Vinding Function And Quantity:
primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Vinding Operating Current:
78.5 milliamperes ac single component single secondary
Vinding Operating Voltage:
30.40 ac volts single component single secondary and 44.00 ac volts single component single secondary and 70.00 ac volts single
component single secondary and 158.00 ac volts single component single secondary
Thread Series Designator:
Jnc single group
Ferminal Type And Quantity:
etab, solder lug
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:

No

NSN 5950-00-834-5089

Power Transformer - Page 2 of 2



Fiig:

A058b0