NSN 5950-00-834-7271

Saturable Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-834-7271

Reliability Indicator:
Not established
Overall Length:
6.190 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.469 inches and 4.531 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
4.219 inches and 4.281 inches single mounting facility single center group
Overall Height:
5.880 inches
Overall Width:
5.500 inches
Frequency Rating:
400.0 hertz single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Height:
5.000 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
2 primary and 2 control single component
Thready Qty Per Inch (tpi):
20 single group
Thread Size:
0.250 inches single group
Dc Resistance Rating In Ohms:
55.000 single component 1st control
Winding Operating Voltage:
206.00 ac volts single component all primary
Special Features:
Control winding no. 2 is a feedback winding, terminals 7 and 8
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
8 turret
Shelf Life:
N/a

NSN 5950-00-834-7271

Saturable Reactor - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0

