

View Online at <https://aerobasegroup.com/nsn/5950-00-835-9430>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.687 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Mounting Slot Width:

0.250 inches single group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

6.187 inches

Body Width:

4.812 inches

Body Height:

3.968 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Power Rating:

450.0 volts-amperes single component single secondary

Winding Operating Voltage:

7.62 ac volts single component single primary and 93.09 ac volts single component single primary and 98.57 ac volts single component single primary and 104.05 ac volts single component single primary and 109.52 ac volts single component single primary and 115.00 ac volts single component single primary

Special Features:

Case metal material

Terminal Type And Quantity:

10 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0