

View Online at <https://aerobasegroup.com/nsn/5950-00-835-9430>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.687 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Mounting Slot Width:**

0.250 inches single group

**Frequency Rating:**

50.0 hertz single component and 400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

6.187 inches

**Body Width:**

4.812 inches

**Body Height:**

3.968 inches

**Inclosure Type:**

Partially enclosed, double shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and slot single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Power Rating:**

450.0 volts-amperes single component single secondary

**Winding Operating Voltage:**

7.62 ac volts single component single primary and 93.09 ac volts single component single primary and 98.57 ac volts single component single primary and 104.05 ac volts single component single primary and 109.52 ac volts single component single primary and 115.00 ac volts single component single primary

**Special Features:**

Case metal material

**Terminal Type And Quantity:**

10 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0