NSN 5950-00-835-9947

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-835-9947

| • |
|---|
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 2.560 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.125 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.000 inches single mounting facility single center group |
| Overall Height: |
| 2.875 inches |
| Overall Width: |
| 1.500 inches |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 56.00 millihenries single component single winding |
| Body Length: |
| 2.560 inches |
| Body Width: |
| 1.500 inches |
| Body Height: |
| 2.875 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |

Winding Operating Current:

1.65 amperes dc single component single winding

Dc Resistance Rating In Ohms:

1.250 single component single winding

Thread Series Designator:

Unc single group

NSN 5950-00-835-9947

Reactor - Page 2 of 2



| i ei ii ii iai Tybe And Quantity. | Tε | rminal | Type | And | Quantity: | |
|-----------------------------------|----|--------|------|-----|-----------|--|
|-----------------------------------|----|--------|------|-----|-----------|--|

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0