# NSN 5950-00-835-9950

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-835-9950

## Reliability Indicator:

Not established

## **Frequency Rating:**

400.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single component

## Winding Shielding Method:

Internal shield grounded to inclosure single component

#### **Body Length:**

1.500 inches

**Body Width:** 

1.200 inches

## **Body Height:**

2.250 inches

## **Distance Between Mounting Facility Centers:**

0.500 inches single mounting facility single center group

## Inclosure Type:

Hermetically sealed

## **Mounting Facility Quantity:**

2 single group

## Mounting Method:

Threaded stud single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

## Thready Qty Per Inch (tpi):

32 single group

## Thread Size:

0.138 inches single group

## Winding Operating Current:

10.0 milliamperes ac single component single secondary

## Winding Power Rating:

2.3 volts-amperes single component single secondary

## Winding Operating Voltage:

235.00 ac volts single component single secondary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

4 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5950-00-835-9950

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

