

View Online at <https://aerobasegroup.com/nsn/5950-00-837-2357>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Maximum Transformer Power Rating:

3.6 milliwatts single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

1.312 inches

Body Width:

1.312 inches

Body Height:

1.750 inches

Maximum Operating Temp:

65.0 degrees celsius

Distance Between Mounting Facility Centers:

1.250 inches single mounting facility all center groupings

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Tinned wire leads

Thread Size:

0.138 inches all groupings

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

4 wire lead

Specification Data:

10001-1028946 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0