NSN 5950-00-837-9952

Saturable Reactor - Page 1 of 2

Reliability Indicator:



View Online at https://aerobasegroup.com/nsn/5950-00-837-9952

| Not established |
|---|
| Overall Length: |
| 1.750 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.344 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.250 inches single mounting facility single center group |
| Overall Height: |
| 3.126 inches |
| Overall Width: |
| 1.625 inches |
| Frequency Rating: |
| 60.0 hertz single component |
| Body Height: |
| 2.688 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 3 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary and 1 control single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Dc Resistance Rating In Ohms: |
| 400.000 single component single control |
| Winding Operating Voltage: |
| 110.00 ac volts single component single primary |
| Special Features: |
| Heater on terminal 6.7, terminal 4 grounded |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 7 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-00-837-9952

Saturable Reactor - Page 2 of 2



| _ | | | | | | |
|----|-----|---------|-----|-----|----|--|
| 11 | em) | tor | 172 | + 1 | nn | |
| | | | | | | |

No

Fiig:

A058b0