NSN 5950-00-838-9223

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-838-9223

| Reliability Indicator: | | | | | |
|---|--|--|--|--|--|
| Not established | | | | | |
| Overall Length: | | | | | |
| 1.156 inches | | | | | |
| Turn Quantity: | | | | | |
| 22 single component single winding | | | | | |
| Overall Height: | | | | | |
| 0.312 inches | | | | | |
| Overall Width: | | | | | |
| 0.609 inches | | | | | |
| Inductance Rating: | | | | | |
| 2.80 microhenries single component single winding | | | | | |
| Coil Form Type: | | | | | |
| Hollow single component | | | | | |
| Core Construction: | | | | | |
| Powdered single component | | | | | |
| Adjustment Device Drive Type: | | | | | |
| Slotted screw single component | | | | | |
| Body Length: | | | | | |
| 1.156 inches | | | | | |
| Inclosure Type: | | | | | |
| Fully enclosed | | | | | |
| Mounting Facility Quantity: | | | | | |
| 1 single group | | | | | |
| Mounting Method: | | | | | |
| Threaded hole single group | | | | | |
| Rating Method: | | | | | |
| Winding turns single component single winding | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 40 single group | | | | | |
| Thread Size: | | | | | |
| 0.112 inches single group | | | | | |
| Winding Conductor Size: | | | | | |
| 0.00893 inches american wire gage single component single winding | | | | | |
| Adjustment Method And Quantity: | | | | | |
| 1 adjustable core single component | | | | | |
| Thread Series Designator: | | | | | |
| Unc single group | | | | | |
| Terminal Type And Quantity: | | | | | |
| 2 tab, solder lug | | | | | |
| Shelf Life: | | | | | |

N/a

NSN 5950-00-838-9223

Radio Frequency Coil - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0