

View Online at <https://aerobasegroup.com/nsn/5950-00-839-2864>

Thread Direction (non-core):

Right-hand single group

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

40.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.996 inches

Body Width:

1.996 inches

Body Height:

1.875 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

20.0 milliamperes ac single component single secondary

Winding Operating Voltage:

89.00 ac pounds per hour wet single component single secondary and 102.00 ac pounds per hour wet single component single secondary and 107.00 ac pounds per hour wet single component single secondary and 110.00 ac pounds per hour wet single component single secondary and 112.00 ac pounds per hour wet single component single secondary and 113.00 ac pounds per hour wet single component single secondary and 115.00 ac pounds per hour wet single component single secondary and 116.00 ac pounds per hour wet single component single secondary and 118.00 ac pounds per hour wet single component single secondary and 120.00 ac pounds per hour wet single component single secondary and 123.00 ac pounds per hour wet single component single secondary and 128.00 ac pounds per hour wet single component single secondary and 141.00 ac pounds per hour wet single component single secondary

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization: