NSN 5950-00-839-8109

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-839-8109

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.875 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.438 inches single mounting facility single center group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 2.30 henry single component single winding |
| Frequency Rating: |
| 60.0 hertz single component |
| Body Length: |
| 2.375 inches |
| Body Width: |
| 2.109 inches |
| Body Height: |
| 2.000 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Dc Resistance Rating In Ohms: |
| 60.000 single component single winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure |

--

NSN 5950-00-839-8109

Reactor - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0