

View Online at <https://aerobasegroup.com/nsn/5950-00-841-9190>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

4.375 inches

Body Width:

2.156 inches

Body Height:

3.609 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

630.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

430.00 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0