NSN 5950-00-842-0103Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-842-0103
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.125 inches single group
Frequency Rating:
50.0 hertz single component and 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
2.375 inches
Body Width:
1.500 inches
Body Height:
2.000 inches
Distance Between Mounting Facility Centers:
2.000 inches single mounting facility single center group
End Application:
Blue ridge class lcc-19, nimitz class cvn, forrestal class cv, iwo jima class lph, mars class t-afs 1, supply class aoe. An/srn-2 (v) navigation
radio set. Submarine (ssn) fire control sys. Submarine interior communication system.
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
1.0 amperes ac single component single secondary
Winding Power Rating:
6.3 volts-amperes single component single secondary
Criticality Code Justification:
Feat
Winding Operating Voltage:
6.30 ac volts single component single secondary
Special Features:
Weapon system essential
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:

NSN 5950-00-842-0103

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0