## NSN 5950-00-842-3266

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-842-3266

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

### Frequency Rating:

55.0 hertz single component and 400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

5.000 inches

#### **Body Width:**

4.750 inches

#### **Body Height:**

6.000 inches

## **Maximum Operating Temp:**

85.0 degrees celsius

## Inclosure Type:

Hermetically sealed

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded stud single group

## **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

## Thready Qty Per Inch (tpi):

20 single group

#### **Thread Size:**

0.250 inches single group

## **Winding Operating Current:**

600.0 milliamperes ac single component 2nd secondary

## **Winding Operating Voltage:**

6.30 ac volts single component 2nd secondary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

11 tab, solder lug

## Shelf Life:

N/a

# **NSN 5950-00-842-3266**Power Transformer - Page 2 of 2



	Of			

Demilitarization:

No

Fiig:

A058b0