NSN 5950-00-843-1772

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-843-1772

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.672 inches single mounting facility single center group and 1.704 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.422 inches single mounting facility single center group and 1.454 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

2.00 millihenries single component single winding

Frequency Rating:

60.0 hertz single component

Body Length:

Between 2.188 inches and 2.312 inches

Body Width:

Between 1.938 inches and 2.062 inches

Body Height:

Between 2.938 inches and 3.125 inches

Winding Quantity:

1 single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single winding

Thread Size:

0.138 inches single group

Winding Operating Current:

200.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

73.000 single component single winding

Test Data Document:

10001-1651663 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 wire hook

Shelf Life:

N/a

NSN 5950-00-843-1772

Reactor - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0