

View Online at <https://aerobasegroup.com/nsn/5950-00-843-2532>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.282 inches single mounting facility single center group and 3.344 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.657 inches single mounting facility single center group and 2.719 inches single mounting facility single center group

**Frequency Rating:**

47.5 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

Between 4.282 inches and 4.344 inches

**Body Width:**

Between 3.657 inches and 3.719 inches

**Body Height:**

Between 5.532 inches and 5.594 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

2 primary single component and 5 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

3.0 amperes ac single component 3rd secondary

**Winding Power Rating:**

45.6 volts-amperes single component 1st secondary

**Winding Operating Voltage:**

6.30 ac volts single component 3rd secondary

**Special Features:**

Two primary windings and five secondary windings

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0