

View Online at <https://aerobasegroup.com/nsn/5950-00-844-9135>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Mounting Hole Diameter:

0.196 inches single group

Frequency Rating:

320.0 hertz single component and 480.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.750 inches

Body Width:

1.620 inches

Body Height:

2.125 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

20.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

122.00 ac pounds per hour with retaining chain single component single primary

Special Features:

78 v and 5.2 v secondaries have one common terminal

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0