NSN 5950-00-846-3744

Power Transformer - Page 1 of 2

Reliability Indicator:

No



View Online at https://aerobasegroup.com/nsn/5950-00-846-3744

| Not established |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.047 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.734 inches single mounting facility single center group |
| Overall Height: |
| 6.000 inches |
| Overall Width: |
| 4.000 inches |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 4.688 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 20 single group |
| Thread Size: |
| 0.250 inches single group |
| Winding Operating Current: |
| 7.0 amperes ac single component 2nd secondary |
| Winding Operating Voltage: |
| 70.00 ac volts single component 2nd secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5950-00-846-3744Power Transformer - Page 2 of 2



Fiig:

A058b0