

View Online at <https://aerobasegroup.com/nsn/5950-00-848-6319>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.985 inches single mounting facility single center group and 2.015 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.047 inches single mounting facility single center group and 1.077 inches single mounting facility single center group

Mounting Hole Diameter:

0.181 inches single group and 0.193 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 2.328 inches and 2.358 inches

Body Width:

Between 1.623 inches and 1.625 inches

Body Height:

Between 2.370 inches and 2.375 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

0.4 milliamperes ac single component single primary

Winding Operating Voltage:

60.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0