NSN 5950-00-848-8446

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-848-8446
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.297 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.859 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core single component
Body Length:
3.060 inches
Body Width:
2.620 inches
Body Height:
4.200 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.164 inches single group
Winding Operating Current:
690.0 milliamperes ac single component single secondary
Winding Operating Voltage:
$24.20 \ \text{ac volts} \ \ \text{single component single secondary and } 26.30 \ \text{ac volts} \ \ \text{single component single secondary and } 28.40 \ \text{ac volts} \ \ \text{single}$
component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
12 tab, solder lug
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5950-00-848-8446

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0