

View Online at <https://aerobasegroup.com/nsn/5950-00-853-0699>

Thread Class (non-core):

2a single group

Thread Direction (non-core):

Right-hand single group

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.688 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

4.688 inches

Body Width:

4.000 inches

Body Height:

6.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

490.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

55.00 ac pounds per hour wet single component 1st secondary

Thread Series Designator:

Uns single group

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0